

Hot Air Seam Sealing Machine

HTM-3788 LDi

Characteristics

1. UP / DOWN ROLLER PREPORTIONAL SPEED CONTROL SYSTEM
2. PROTECTOR FOR WORKER & FABRICS FROM HOT NOZZLE
3. AUTOMATIC VOLTAGE REGULATOR SYSTEM (AVR) IN CHANGEABLE ENVIRONMENT FROM 180v TO 260v
4. ERROR MESSAGE FOR HEATING PROBLEM IN LCD DISPLAY PANNEL
5. SLIDE CAM STYLES NOZZLE MOVEMENT
6. LCD DISPLAY PANNEL
7. CONTROLLER FOR NOZZLE : UP, DOWN, RIGHT, LEFT, SCALE
8. UPPER ROLLER STROKE & SCALE FOR ROLLERS CENTER
9. UPPER / DOWN ROLLERS CHAIN TENSION CONTROL SYSTEM
10. NEW DESIGN-SOFT MOVEMENTS FOOT PEDAL
11. AUTO CONTROLLER FOR TAPE TENSION
12. NOZZLE ANGLE CONTROLLER
13. AUTO COOLING
14. AUTO TAPE CUTTING SYSTEM
15. USE OF 2&3 LAYER
16. FORWARD / REVERSE ROTATION
17. BACKLASHING STOP
18. FEEDING TYPE CUTTER
19. WORKING LIGHT
20. INDICATION FOR THE CUTTING POINT & SEAM SEALING CENTER-OPTION
21. UPPER ROLLER HEATING-OPTION

Specification

Power requirement	Single/Triple Phase 220V±10% 50/60Hz
Electric Consumption	1.5KVA
Compressed Air	2.2KW
Width of adhesive tape	12~23mm(Optional extra)
Upper roller lift	30mm / Optional extra
Speed	1~18M/min. Digital read-out of operating speed
MAX Temperature	Up to 699°C
Heater Capacity	3600W