

# Hot Air Seam Sealing Machine HTM-5533 LDi

## Characteristics

1. UPPER & DOWN ROLLER PROPORTIONAL SPEED ADJUSTMENT SYSTEM (DUAL MOTOR)
2. LCD DISPLAY PANNEL
3. SLIDE CAM STYLE'S NOZZLE MOVEMENT
4. ERROR MESSAGE FOR HEATER PROBLEM
5. EMERGENCY SYSTM FOR HEATER'S OVER VOLTAGE
6. NEW DESIGN, SOFT MEVEMENT'S FOOT PEDAL
7. UPPER/DOWN ROLLER'S CHAIN TENSION CONTROL SYSTEM
8. AUTO STOP WHEN GOODS ARE ROLLED UP
9. AUTO CONTROLLER FOR TAPE TENSION
10. NOZZLE ANGLE CONTROLLER
11. AUTO COLLING
12. AUTO TAPE CUTTING SYSTEM
13. USE OF 2&3 LAYER
14. FORWARD / REVERSE ROTATION
15. BACKLASHING STOP
16. SAFETY FOR NOZZLE COVER
17. FEEDING TYPE CUTTER
18. INDICATION FOR THE CUTTING POINT & SEAM SEALING CENTER (OPTION)
19. UPPER ROLLER HEATING (OPTION)

## Specification

Power requirement	Single/Triple Phase 220V±10% 50/60Hz
Electric Consumption	1.5KVA
Compressed Air	2.2KW
Width of adhesive tape	12~23mm(Optional extra)
Upper roller lift	30mm / Optional extra
Speed	1~18M/min. Digital read-out of operating speed
MAX Temperature	Up to 699°C
Heater Capacity	3600W