

Electronic Bartack Machine

SP-430GA-01/02

40 × 30mm

Electric Button/Attaching Machine

SP-438GA

6.4 × 6.4mm



- 改善了夹线系统，即使缝纫开始时不减速也可防止产生面线脱线
 Improved nipper reduces thread cast-off at the sewing start.
- 缩短切线后针线余线，可有效防止在缝纫开始时出现鸟巢状线迹，
 进一步提高了缝纫品质
 Shorter thread end after cutting efficiently reduces bird nesting at sewing start, which
 improves sewing quality in return.

01用于中厚料的缝纫，02用于厚料的缝纫；主要应用于服装行业中的各种男女装，牛仔布，针织物，女士内衣，箱包类，两款型号缝制区域均为40 × 30mm。

01 for medium-thick material, 02 for thick material; Mainly used in men's and women's clothes, denim, knitwear, women's underwear and bag series. Both types have sewing area 40 × 30mm.



NINGBO SUPREME ELECTRONIC MACHINERY INC.

Bangladesh Office:
 House # 58, Floor # 1A, Road # 12,
 Sector # 10, Uttara, Dhaka-1230
 Cell: +880 1715-941899
 E-mail: mizanbd@tosupreme.com
 www.china-supreme.com

Chattogram Office:
 Parabat Center(5th Floor),
 472 5K Mujib Road
 Chowmohani, Agrabad, Chattogram.
 E-mail: chittagongbdt@tosupreme.com
 salesbd@tosupreme.com



型号 Model	平缝 Flat Seam	包边包线 Standard edge stitching	缝边缝边 Sewing edge	针距 Stitching length	立线缝剪 Cutting Device	打线装置 Thread clamping device	最高缝速 Highest sewing speed
SP-430GA	★	★	40 × 30mm	0.05 - 12.7mm	★	★	3,200 rpm
SP-438GA	★	★	6.4 × 6.4mm	0.05 - 12.7mm	★	★	2,700 rpm

型号 Model	SP-430GA							SP-438GA	SP-438GA	SP-430G-08
	01	02	02Q	03	05	06	06QD			
用途 Application	电子卷边机 Electronic Neck Machine	气动打孔包边机 Pneumatic hole sewing machine	西服肩肩骨线机 Jacket shoulder bone sewing system	电子排线缝边机 Electronic Edge finish fabric machine	气动排线缝边机 Pneumatic edge finish fabric machine	电子卷边机 Electronic Neck Machine	打平机 Flat fabric pressing machine	打立机 Turnlike machine machine	自动包边机 Automatic edge sewing machine	
缝迹 Line	单针平缝 Single-needle flat seam									
最高缝速 Highest sewing speed	3,200 rpm						2,700 rpm		3,200 rpm	
缝制区域(X × Y) Sewing area	40 × 30mm	10 × 10mm	24 × 3mm	6 × 40mm		40 × 3mm	6.4 × 6.4mm	3.4 × 0mm	40 × 30mm	
应缝制扣尺寸 Dimensions of button	-						φ-30mm	直径 < 18mm	-	
送布装置 Cloth feeding device	间歇送布 (脉冲马达驱动) Intermitent feeding (driven by pulse motor)									
针距 Stitch Length	0.05 - 12.7mm									
最大针数 Maximum stitch amount	5000针/1个图案 (5000 needles/1 pattern)									
驱动方式 Drive mode	脉冲马达驱动 Pulse motor drive									
压线上升量 Rising amount of ironer line adjuster	最大 Max. 17mm									
压线上升量 Button grip lifting amount	-						最大 Max. 13mm		-	
旋梭 Hook	半自动标准旋梭 / Semi-Rotary standard shuttle hook								前梭 / Front type	
电子夹线器 Electronic wire clamping device	标准装备 / Standard facility									
立线装置 Thread Clamping Device	标准装备 / Standard facility									
夹线装置 Thread clamping device	标准装备 / Standard facility									
切线装置 Cutting device	标准装备 / Standard facility									
数据储存方式 Quantity of data storage	闪存 (使用CF卡可任意增加容量) Flash memory (with CF card you can have all systems you like)									
外部数据储存媒体 External data storage media	CF卡 / CF card									
循环程序数 Number of cycle programs	30个循环 (共50个程序) / 30 cycles (50 programs for each)									
存储数据量 Number of stored data	29种缝纫图案 / 29 kinds of sewing patterns						49种图案 49 kinds of sewing patterns		-	
马达 Motor	AC伺服马达 550W AC servomotor 550W									
重量 Weight	机头: 约64 kg 操作台: 约30 kg 控制箱: 20 kg (根据出口国家不同) Head: about 64 kg Table & stand: about 30 kg Control Box: 20 kg (according to different export countries)								机头: 64kg Above stand: 40kg	
电源 Power	单相 220V, 3相 380V Single phase 220V, 3-phase 380V								三相 380V 50Hz 380V 50Hz	
气压 Air pressure	0.5Mpa (1.7kg/cm ²)									

以上数据仅供参考, 详细情况请洽销售经理。
The above data are only for reference, any detail please contact local distributor for details.

为了安全, 产品说明书有变更, 恕不另行通知, 为安全起见, 请详读产品使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.